

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 6 : A47B 3/06, 3/091, 3/00, 9/14	A1	(11) International Publication Number: WO 95/10204
		(43) International Publication Date: 20 April 1995 (20.04.95)

(21) International Application Number: PCT/CA94/00563

(22) International Filing Date: 7 October 1994 (07.10.94)

(30) Priority Data:
08/136,186 15 October 1993 (15.10.93) US

(71) Applicant: INO-PRODUCTS INC. [CA/CA]; 460 Old Orchard Grove, North York, Ontario M5M 2G4 (CA).

(72) Inventor: SOPER, Douglas; 460 Old Orchard Grove, North York, Ontario M5M 2G4 (US).

(74) Agent: DELBRIDGE, Robert, F.; Rogers & Scott, 214 Randall Street, Oakville, Ontario L6J 1P7 (CA).

(81) Designated States: AM, AT, AU, BB, BG, BR, BY, CA, CH, CN, CZ, DE, DK, ES, FI, GB, GE, HU, JP, KE, KG, KP, KR, KZ, LK, LT, LU, LV, MD, MG, MN, MW, NL, NO, NZ, PL, PT, RO, RU, SD, SE, SI, SK, TJ, TT, UA, UZ, VN, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG), ARIPO patent (KE, MW, SD, SZ).

Published


With international search report.

Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.

(54) Title: FOLDING TABLE

(57) Abstract

A folding table has a table top of synthetic plastic material with an upper working surface and an underside, the underside having at least one rearwardly located leg retainer and at least one forwardly located strut retainer. A leg assembly has an elongated connecting member and a pair of legs extending from opposite ends of the connecting member, each leg having a foot member extending from a lower end thereof remote from the connecting member. An angularly movable strut is pivotally secured at the rear to at least one of the legs and is releasably engageable at the front with the strut retainer. The strut is angularly moveable between a working position in releasable engagement with the strut retainer to maintain the tabletop in a working position and a retracted position between the legs when released from the strut retainer. The or each leg retainer retains the connecting member in engagement therewith while permitting angular movement of the table top between a working position and a folded position in which the table top is substantially parallel to the legs.



BEST AVAILABLE COPY

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	GB	United Kingdom	MR	Mauritania
AU	Australia	GE	Georgia	MW	Malawi
BB	Barbados	GN	Guinea	NE	Niger
BE	Belgium	GR	Greece	NL	Netherlands
BF	Burkina Faso	HU	Hungary	NO	Norway
BG	Bulgaria	IE	Ireland	NZ	New Zealand
BJ	Benin	IT	Italy	PL	Poland
BR	Brazil	JP	Japan	PT	Portugal
BY	Belarus	KE	Kenya	RO	Romania
CA	Canada	KG	Kyrgyzstan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SI	Slovenia
CI	Côte d'Ivoire	LI	Liechtenstein	SK	Slovakia
CM	Cameroon	LK	Sri Lanka	SN	Senegal
CN	China	LU	Luxembourg	TD	Chad
CS	Czechoslovakia	LV	Latvia	TG	Togo
CZ	Czech Republic	MC	Monaco	TJ	Tajikistan
DE	Germany	MD	Republic of Moldova	TT	Trinidad and Tobago
DK	Denmark	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	US	United States of America
FI	Finland	MN	Mongolia	UZ	Uzbekistan
FR	France			VN	Viet Nam
GA	Gabon				

FOLDING TABLE

This invention relates to folding tables.

There are of course many known different kinds of folding tables. However, there is still a need for a versatile folding table which is of simple yet
5 attractive construction and which can be easily erected and folded.

According to the invention, a folding table comprises a table top of synthetic plastic material having an upper working surface and an underside, the underside having at least one rearwardly located leg retainer and at least one forwardly located strut retainer, a leg assembly comprising an elongated connecting
10 member and a pair of legs extending from opposite ends of the connecting member, each leg having a foot member extending from a lower end thereof remote from the connecting member and an angularly moveable strut pivotally secured at the rear to at least one of the legs and releasably engageable at the front with the strut
15 retainer. The strut is angularly moveable between a working position in releasable engagement with the strut retainer to maintain the table top in a working position and a retracted position between the legs when released from the strut retainer. The or each leg retainer retains the connecting member in engagement therewith while permitting angular movement of the table top between a working position and a folded position in which the table top is substantially parallel to the legs.

20 The underside of the table top may have a laterally-spaced pair of rearwardly located leg retainers, and the or each leg retainer may retain the connecting member in releasable snapping engagement therewith. The or each leg retainer may comprise a closely spaced pair of substantially identical leg retainer members which each retain the connecting member in engagement therewith.

25 The underside of the table top may have a laterally-spaced pair of forwardly located strut retainers, and the or each strut retainer may receive the strut in

releasable snapping engagement therewith. The or each strut retainer may receive the strut in releasable engagement therewith at a plurality of positions spaced from one another in a front to rear direction. The or each strut retainer may comprise a closely-spaced pair of substantially identical strut retainer members which each receive the strut in releasable engagement therewith.

The strut may comprise a pair of laterally-spaced side members each pivotally secured at a rear end to a respective leg and a transverse member extending between the front ends of the side members, the transverse member being received by the or each strut retainer in releasable engagement therewith in the working position. The legs may each have upper and lower portions in telescoping engagement, the lower leg portions being securable at different longitudinal positions relative to the upper portions to vary the length of the legs.

The lower leg portions may be angularly movable relative to the upper leg portions about the longitudinal axes of the legs, the lower leg portions being securable in working positions in which the foot members are parallel to one another and folded positions in which the foot members extend in opposite directions side-by-side one another.

One embodiment of the invention will now be described, by way of example, with reference to the accompanying drawings, of which

Fig. 1 is a perspective view of a folding table in accordance with one embodiment of the invention, the table top being in a horizontal working position,

Fig. 2 is a detailed view of the portion of a table leg indicated by the arrow 2 in Fig. 1,

Fig. 3 is a perspective view of the table with the table top in an inclined working position and showing the underside of the table top,

SUBSTITUTE SHEET

catch member 42 adjacent its lower end as shown in Fig. 2. The catch member 42 has a pair of projections 44 which project through apertures 46 in the upper leg portion 38 on opposite sides thereof. The projections 44 are snappingly engageable in selected pairs of apertures 40 in the lower leg portions 38 to enable the length of the legs 24, 26 to be adjusted as indicated in dotted outline in Fig. 1.

For folding purposes, as will be described in more detail later, the lower leg portions 38 can be rotated about their longitudinal axis to the laterally-inwardly extending positions shown in dotted outline in Fig. 3. Each lower leg portion 38 also has an aperture 48 on a front surface so that one of the projections 44 can snap thereinto to retain the lower leg portions 38 in the inwardly folded position.

An angularly movable strut 50 is pivotally secured at the rear to the upper leg portions 36. The strut 50 is a metal rod bent to provide a transverse member 51 at the front and a pair of laterally-spaced side members 52 extending rearwardly from opposite ends thereof. Each side member 52 has a bent free end portion 54 at the rear extending into an aperture 56 in the respective upper leg portion 36 to pivotally secure the strut 50 thereto. Each strut retainer 20 comprises a closely-spaced pair of identical strut retainer members 58 which each have a series of hook portions 60 spaced from one another in the front to rear direction which can each retain the transverse strut member 51 in releasable snapping engagement therewith.

Fig. 1 shows the table in the fully erected position with the table top 12 horizontal. It will be understood that to retain the table top 12 in the horizontal position, the transverse strut member 51 is snapped in to the strut retainer hook portion 60 furthest from the front of the table top 12. The foot members 28, 30 extend forwardly from the legs 24, 26 beneath the table top 12. If it is desired to position the table top 12 in an inclined manner as indicated in dotted outline in Fig.

SUBSTITUTE SHEET

Fig. 4 is a perspective view of the table in the fully folded condition.

Fig. 5 is a sectional detail view along the line 5-5 of Fig. 3 of a rear portion of a table top showing a leg retainer and part of the leg assembly, and Fig. 6 is a similar view along the line 6-6 of Fig. 3 of a front portion of the table top showing a strut retainer and part of the strut.

Referring to the drawings, a folding table 10 has an integrally molded plastic table top 12 in the form of a rectangular panel with rounded corners, the table top 12 having an upper working surface 14 and an underside 16. The underside 16 has a laterally-spaced pair of rearwardly located integral leg retainers 18 and a laterally-spaced pair of forwardly located integral strut retainers 20. A leg assembly 22 of tubular steel comprises a transverse connecting member 23 and a pair of legs 24, 26 extending from opposite ends of the connecting member 23, each leg 24, 26 having an elongated foot member 28, 30 respectively extending from the lower end thereof.

Each leg retainer 18 comprises a closely-spaced pair of identical leg retainer members 32 which each have hook portions 34 to retain the connecting member 23 in releasable snapping engagement therewith and permit the table top 12 to be moved angularly relative to the leg assembly 22 in a manner which will be described in more detail later.

Each leg 24, 26 has upper and lower portions 36, 38 in telescopic engagement, the lower leg portions 38 being slidable over the upper leg portions 36. Each upper leg portion 36 is integral with the relevant end of the connecting member 23, and each lower leg portion 38 is integral with the respective foot member 28, 30, the foot members 28, 30 thus also being of tubular steel. Each lower leg portion 38 has a series of vertically-spaced apertures 40 on its laterally outer and inner sides, and each upper leg portion 36 contains a resilient U-shaped

1 and shown in more detail in Fig. 3, the transverse strut member 51 is snapped into strut hook portions 60 nearer the front of the table top 12.

The table can be completely folded as shown in Fig. 4, by swinging the foot members 28, 30 inwardly as previously described and releasing the transverse strut retainer 51 from the retainer hook portions 60 and permitting the strut 50 to pivot downwardly to a near vertical position. The table top 12 can then be permitted to swing downwardly in the same manner.

The foot members 28, 30 can be left in the forwardly extending position shown in Figs. 1 and 3, and the strut 50 and table top 12 put in the near vertical position so that the members 28, 30 can be slid under the side or rear of a chair or couch with the table top 12 adjacent the side or rear of the chair or couch. The table is thus then readily accessible for future use, it merely being necessary to slide the table out and position the table top 12 by means of the strut 50.

It will be clear from the above description of a preferred embodiment that the present invention provides a folding table which is of simple yet attractive construction and which can be easily erected and folded.

Other embodiments of the invention will be readily apparent to a person skilled in the art, the scope of the invention being defined in the appended claims.

We Claim

1. A folding table comprising:
 - a table top of synthetic plastic material having an upper working surface and an underside,
 - said underside having a laterally spaced pair of rearwardly located integral leg retainers and a laterally spaced pair of forwardly located integral strut retainers,
 - a leg assembly comprising an elongated connecting member and a pair of legs extending from opposite ends of the connecting member, each leg having a foot member extending from a lower end thereof remote from the connecting member, and
 - an angularly movable strut pivotally secured at a rear end thereof to at least one of the legs and releasably engageable at a front end thereof with the strut retainers,
 - each integral leg retainer comprising a closely spaced pair of substantially identical integral leg retainer members which each retain the connecting members in snapping engagement therewith and
 - each integral strut retainer comprising a closely spaced pair of substantially integral strut retainer members which each receive the strut in releasable engagement therewith,
 - said strut being angularly moveable between a working position in releasable engagement with the strut retainers to maintain the tabletop in a working position and a retracted position between the legs when released from the strut retainers,
 - each leg retainer retaining the connecting member in releasable snapping engagement therewith while permitting angular movement of the table top between a working position and a folded position in which the table top is substantially parallel to the legs.
2. A folding table according to claim 1 wherein each strut retainer

SUBSTITUTE SHEET

receives the strut in releasable snapping engagement therewith.

3. A folding table according to claim 1 wherein each strut retainer can receive the strut in releasable engagement therewith at a plurality of positions spaced from one another in a front to rear direction.
4. A folding table according to claim 1 wherein the strut comprises a pair of laterally-spaced side members each pivotally secured at a rear end to a respective leg and a transverse member extending between the front ends of the side members, said transverse member being received by each strut retainer in releasable engagement therewith in the working position.
5. A folding table according to claim 1 wherein said legs each have upper and lower portions in telescoping engagement, the lower leg portions being securable at different longitudinal positions relative to the upper portions to vary the length of the legs.
6. A folding table according to claim 5 wherein the lower leg portions are angularly moveable relative to the upper leg portions about the longitudinal axes of the legs, the lower leg portions being securable in working positions in which the foot members are parallel to one another and folded positions in which the foot members extend in opposite directions side-by-side one another.

1/3







FIG. 1

FIG. 2





SUBSTITUTE SHEET

2/3



SUBSTITUTE SHEET



INTERNATIONAL SEARCH REPORT

International Application No
PCT/CA 94/00563

A. CLASSIFICATION OF SUBJECT MATTER

IPC 6 A47B3/06 A47B3/091 A47B3/00 A47B9/14

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 A47B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	FR,A,1 269 036 (HOLZMANN) 29 June 1961 see the whole document ----	1
A	US,A,2 857 227 (JACQUES) 21 October 1958 see figures 1-2 ----	1,6
A	US,A,2 902 325 (KNOBLOCK) 1 September 1959 see the whole document ----	1
A	US,A,3 108 550 (KNOBLOCK) 29 October 1963 see the whole document ----	1
A	FR,A,1 279 355 (JAMES) 13 November 1960 see figures 1-3 ----	1,2
A	BE,A,675 656 (BREMSHEY & CO) 16 May 1966 see figures 2,4-6 -----	1,5

☐ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *&* document member of the same patent family

Date of the actual completion of the international search

13 February 1995

Date of mailing of the international search report

03.03.95

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+ 31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+ 31-70) 340-3016

Authorized officer

Noesen, R

INTERNATIONAL SEARCH REPORT

Internat'l Application No
PCT/CA 94/00563

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
FR-A-1269036		CH-A- 388563 DE-B- 1160146	
US-A-2857227	21-10-58	NONE	
US-A-2902325	01-09-59	NONE	
US-A-3108550	29-10-63	US-A- 3217673 US-A- 3256840	16-11-65 21-06-66
FR-A-1279355		NONE	
BE-A-675656	16-05-66	CH-A- 470860 FR-A- 1540920 GB-A- 1076243 NL-A- 6601189	15-04-69 04-08-66

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☒ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☒ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.